

SAFETY DATA SHEET

PFT657S4 v4.0
en/US



1. Identification of the substance/mixture and of the company/undertaking

Product name	PPI CHAMPAGNE	
Product code	PFT657S4	Formula date: 2016-02-25
Intended use	Coating powder	
	Axalta Coating Systems, LLC Applied Corporate Center 50 Applied Bank Boulevard, Suite 300 US Glen Mills, PA 19342	
Telephone	Product information	(800) 247-3886
	Medical emergency	(855) 274-5698
	Transportation emergency	(800) 424-9300 (CHEMTREC)

2. Hazards identification

This preparation is hazardous per the following GHS criteria

GHS-Classification

Serious eye damage/eye irritation	Category 1
Skin sensitisation	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 2
Target Organ Systemic Toxicant - Repeated exposure	Category 1

GHS-Labeling

Hazard symbols



Signal word: Danger

Hazard statements

- May cause an allergic skin reaction.
- Causes serious eye damage.
- May cause genetic defects.
- Suspected of causing cancer.
- Causes damage to organs through prolonged or repeated exposure.
- May form combustible dust concentrations in air.

Precautionary statements

- Obtain special instructions before use.
- Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
- Do not eat, drink or smoke when using this product.
- Contaminated work clothing should not be allowed out of the workplace.
- Wear protective gloves/protective clothing/eye protection/face protection.
- IF ON SKIN: Wash with plenty of soap and water.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF exposed or concerned: Get medical advice/ attention.
- Immediately call a POISON CENTER/doctor.

SAFETY DATA SHEET

PFT657S4 v4.0
en/US



Specific treatment (see supplemental first aid instructions on this label).
If skin irritation or rash occurs: Get medical advice/ attention.
Wash contaminated clothing before reuse.
Store locked up.
Dispose of contents/container in accordance with local regulations.

Other hazards which do not result in classification

Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. May form explosible dust-air mixture if dispersed.

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity:

0 %

3. Composition/information on ingredients

Mixture of synthetic resins and pigments

Components

CAS-No.	Chemical name	Concentration
13463-67-7	Titanium dioxide	9.8%
2451-62-9	1,3,5- triglycidyl isocyanurate	4 - 15%

Any concentration shown as a range is due to batch variation.

Non-regulated ingredients 80 - 90%

OSHA Hazardous: Yes

4. First aid measures

Eye contact

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

Skin contact

Do NOT use solvents or thinners. Take off contaminated clothing and shoes immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

Inhalation

Avoid breathing dust. Inhalation of dust may cause shortness of breath, tightness of the chest, a sore throat and cough. Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.

Ingestion

If swallowed, seek medical advice immediately and show this safety data sheet (SDS) or product label.

Most Important Symptoms/effects, acute and delayed

Inhalation

Dust generated from this product may be irritating to the respiratory tract.

Ingestion

May result in gastrointestinal distress.

Skin or eye contact

Dust generated from this product may cause irritation of the eyes. Repeated or prolonged contact may cause skin irritation with discomfort and dermatitis.

SAFETY DATA SHEET

PFT657S4 v4.0
en/US



Indication of Immediate medical attention and special treatment needed if necessary

No data available on the product. See section 3 and 11 for hazardous ingredients found in the product.

5. Firefighting measures

Suitable extinguishing media

Water spray/Dry chemical

Extinguishing media which shall not be used for safety reasons

High volume water jet

Hazardous combustion products

CO, CO₂, smoke, and oxides of any heavy metals that are reported in "Composition, Information on Ingredients" section.

Fire and Explosion Hazards

The product is not flammable. The product itself does not burn.

Special Protective Equipment and Fire Fighting Procedures

Full protective flameproof clothing should be worn as appropriate. Wear self-contained breathing apparatus for firefighting if necessary. In the event of fire, cool tanks with water spray. Do not allow run-off from fire fighting to enter public sewer systems or public waterways.

6. Accidental release measures

Procedures for cleaning up spills or leaks

Sweep up material and dispose of properly. Avoid breathing any dust that might be generated. Spills of fine material should be cleaned using gentle sweeping or vacuuming. Cleaning methods (e.g. compressed air) which can generate potentially combustible dust clouds should not be used.

Environmental precautions

Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

7. Handling and storage

Precautions for safe handling

Observe label precautions. Close container after each use. Do not transfer contents to unlabeled containers. Wash thoroughly after handling and before eating or smoking. Precautions should be taken to prevent the formation of dusts in concentrations above flammable, explosive or occupational exposure limits. Keep away from open flames, hot surfaces and sources of ignition. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. If material is a coating: do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves. Combustible dust clouds may be created where operations produce fine material (dust). Avoid formation of significant deposits of material as they may become airborne and form combustible dust clouds. Build up of fine material should be cleaned using gentle sweeping or vacuuming in accordance with best practices. Cleaning methods (e.g. compressed air) which can generate potentially combustible dust clouds should not be used.

Advice on protection against fire and explosion

Always keep in containers of same material as the original one. Airborne dusts are potentially explosive. Avoid formation of significant deposits of material as they may become airborne and form combustible dust clouds. Handling and processing operations should be conducted in accordance with best practices (e.g. NFPA-654). Never use pressure to empty container: container is not a pressure vessel. The accumulation of contaminated rags may result in spontaneous combustion. Good housekeeping standards and regular safe removal of waste materials will minimize the risks of spontaneous combustion and other fire hazards.

Storage

SAFETY DATA SHEET

PFT657S4 v4.0
en/US



Requirements for storage areas and containers

Observe label precautions. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Advice on common storage

Store separately from oxidizing agents and strongly alkaline and strongly acidic materials.

8. Exposure controls/personal protection

Engineering controls and work practices

Do not breathe dust. Provide adequate ventilation. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If these are not sufficient to maintain exposure to dusts below the OEL, suitable respiratory protection must be worn.

National occupational exposure limits

CAS-No.	Chemical name	Source	Time	Type	Value	Note
13463-67-7	Titanium dioxide	OSHA	8 hr	TWA	15 mg/m ³	Total Dust
		Dupont	8 & 12 hour	TWA	10 mg/m ³	Total Dust
		Dupont	8 & 12 hour	TWA	5 mg/m ³	Respirable Dust
2451-62-9	1,3,5- triglycidyl isocyanurate	ACGIH	8 hr	TWA	50 ug/m ³	
		Dupont	8 & 12 hour	TWA	50 ug/m ³	

Glossary

CEIL	Ceiling exposure limit
STEL	Short term exposure limit
TL	Threshold limits
TLV	Threshold Limit Value
TWA	Time weighted average
TWAE	Time-Weighted Average

Protective equipment

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

Respiratory protection

Should any dust be generated, it should not be breathed. If a respirator is needed to meet applicable exposure limits, wear a properly fitted air-purifying respirator approved by NIOSH. Follow respirator manufacturer's directions for respirator use. Do not breathe dust. If respirator is required to meet applicable exposure limits, use a NIOSH approved TC-84A respirator in accordance with regulatory requirements (in the US follow OSHA standard 29CFR1910.134) and the respirator manufacturer's directions.

Eye protection

Desirable in all industrial situations.

Skin and body protection

Gloves are recommended

Hygiene measures

Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Environmental exposure controls

Do not let product enter drains.

For ecological information, refer to Ecological Information Section 12.

9. Physical and chemical properties

SAFETY DATA SHEET

PFT657S4 v4.0
en/US



Appearance

Form: solid **Colour:** tan

Flash point	Not applicable.
Lower Explosive Limit	Not applicable.
Upper Explosive Limit	Not applicable.
Evaporation rate	Not applicable
Vapor pressure of principal solvent	0.0 hPa
Water solubility	nil
Vapor density of principal solvent (Air = 1)	Not applicable.
Approx. Boiling Range	Not applicable.
Approx. Freezing Range	Not applicable.
Gallon Weight (lbs/gal)	12.3
Specific Gravity	1.47
Percent Volatile By Volume	0.00%
Percent Volatile By Weight	0.00%
Percent Solids By Volume	100.00%
Percent Solids By Weight	100.00%
pH (waterborne systems only)	Not applicable
Partition coefficient: n-octanol/water	No data available
Ignition temperature	400 °C DIN 51794
Decomposition temperature	Not applicable.
Viscosity (23 °C)	Not applicable. ISO 2431-1993
VOC* less exempt (lbs/gal)	0.0
VOC* as packaged (lbs/gal)	0.0

Does not sustain combustion.

* VOC less exempt (theoretical) and VOC as packaged (theoretical) are based upon the VOC of the packaged material at the point of manufacture.

10. Stability and reactivity

Stability

Stable

Conditions to avoid

Stable under recommended storage and handling conditions (see section 7).

Materials to avoid

None reasonably foreseeable.

Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

Hazardous Polymerization

Will not occur.

Sensitivity to Static Discharge

No data available

Sensitivity to Mechanical Impact

None known.

11. Toxicological information

Information on likely routes of exposure

Inhalation

Dust generated from this product may be irritating to the respiratory tract.

Ingestion

May result in gastrointestinal distress.

Skin or eye contact

Dust generated from this product may cause irritation of the eyes. Repeated or prolonged contact may cause skin irritation with discomfort and dermatitis.

Delayed and immediate effects and also chronic effects from short and long term exposure:

Acute oral toxicity

Not classified according to GHS criteria

Acute dermal toxicity

not hazardous

Acute inhalation toxicity

not hazardous

% of unknown composition: 0 %

Skin corrosion/irritation

Not classified according to GHS criteria

Serious eye damage/eye irritation

1,3,5- triglycidyl isocyanurate Category 1

Respiratory sensitisation

Not classified according to GHS criteria

Skin sensitisation

1,3,5- triglycidyl isocyanurate Category 1

Germ cell mutagenicity

1,3,5- triglycidyl isocyanurate Category 1B

Carcinogenicity

Titanium dioxide Category 2

Toxicity for reproduction

Not classified according to GHS criteria

Target Organ Systemic Toxicant - Single exposure

Not classified according to GHS criteria

Target Organ Systemic Toxicant - Repeated exposure

- Inhalation

Respiratory system Titanium dioxide

SAFETY DATA SHEET

PFT657S4 v4.0
en/US



Aspiration toxicity

Not classified according to GHS criteria

Numerical measures of toxicity (acute toxicity estimation (ATE),etc.)

No information available.

Symptoms related to the physical, chemical and toxicological characteristics

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar preparations, this preparation may be a skin sensitiser and an irritant. Low molecular epoxy constituents are irritating to eyes, mucous membranes and skin. Repeated skin contact may lead to irritation and to sensitization, possibly with cross-sensitization to other epoxies. Avoid skin and eye contact. Avoid inhalation of vapour or mist.

Whether the hazardous chemical is listed by NTP, IARC or OSHA

Titanium dioxide IARC 2B

12. Ecological information

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses.

13. Disposal considerations

Waste Disposal Method

Do not allow material to contaminate ground water systems. Incinerate or otherwise dispose of waste material in accordance with Federal, State, Provincial, and local requirements. Do not incinerate in closed containers.

14. Transport information

Not classified as dangerous in the meaning of transport regulations.

The transport information is for bulk shipments. Exceptions may apply for smaller containers.

Matters needing attention for transportation

Confirm that there is no breakage, corrosion, or leakage from the container before shipping. Be sure to prevent damage to cargo by loading so as to avoid falling, dropping, or collapse. Ship in appropriate containers with denotation of the content in accordance with the relevant statutes and rules.

15. Regulatory information

TSCA Status

In compliance with TSCA Inventory requirements for commercial purposes.

DSL Status

Product is not DSL listed because one or more ingredients are not on the DSL inventory.

Photochemical Reactivity

Non-photochemically reactive

SAFETY DATA SHEETPFT657S4 v4.0
en/US

CAS #	Ingredient	EPCRA					CERCLA	CAA
		302	TPQ	RQ	311/312	313	RQ(lbs)	HAP

Regulatory information

CAS #	Ingredient	EPCRA					CERCLA	CAA
		302	TPQ	RQ	311/312	313	RQ(lbs)	HAP
13463-67-7	Titanium dioxide	N	NR	NR	A,C,F,N,P,R	N	NR	N
2451-62-9	1,3,5- triglycidyl isocyanu- rate	N	NR	NR	A,C,F,N,P,R	N	NR	N

Key:

EPCRA	Emergency Planning and Community Right-to-know Act (aka Title III, SARA)
302	Extremely hazardous substances
311/312 Categories	F = Fire Hazard R = Reactivity Hazard P = Pressure Related Hazard A = Acute Hazard C = Chronic Hazard
313 Information	Section 313 Supplier Notification - The chemicals listed above with a 'Y' in the 313 column are subject to reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know act of 1986 and of 40 CFR 372.
CERCLA	Comprehensive Emergency Response, Compensation and Liability Act of 1980.
HAP	Listed as a Clean Air Act Hazardous Air Pollutant.
TPQ	Threshold Planning Quantity.
RQ	Reportable Quantity
NA	not available
NR	not regulated

16. Other information

HMIS rating H: 1 F: 0 R: 0

Glossary of Terms:

ACGIH	American Conference of Governmental Industrial Hygienists.
IARC	International Agency for Research on Cancer.
NTP	National Toxicology Program.
OEL	Occupational Exposure Limit
OSHA	Occupational Safety and Health Administration.
STEL	Short term exposure limit
TWA	Time-weighted average.
PNOR	Particles not otherwise regulated.
PNOC	Particles not otherwise classified.

NOTE: The list (above) of glossary terms may be modified.

Notice from Axalta Coating Systems :

The document reflects information provided to Axalta Coating Systems by its suppliers. Information is accurate to the best of our knowledge and is subject to change as new data is received by Axalta Coating Systems. Persons receiving this information should make their own determination as to its suitability for their purposes prior to use.

The information on this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

SDS prepared by: Axalta Coating Systems Regulatory Affairs

SAFETY DATA SHEET

PFT657S4 v4.0

en/US



Report version

Version	Changes
4.0	2, 3, 8, 11, 16

Revision Date: 2018-01-05

(800) 247-3886
axalta.us